

表1 限用物質含有情況超出百分比含量基準值之標示

東元電機股份有限公司						
設備名稱：漏電斷路器，型號（型式）：請見表2						
Equipment name                      Type designation (Type)						
單元Unit	限用物質及其化學符號 Restricted substances and its chemical symbols					
	鉛Lead (Pb)	汞Mercury (Hg)	鎘Cadmium (Cd)	六價鉻 Hexavalent chromium (Cr <sup>+6</sup> )	多溴聯苯 Polybrominated biphenyls (PBB)	多溴二苯醚 Polybrominated diphenyl ethers (PBDE)
外殼、把手、絕緣板	○	○	○	○	○	○
接點	○	○	—	○	○	○
內部機構及零件	—	○	○	○	○	○
電路板	—	○	○	○	○	○
螺絲、配件	○	○	○	○	○	○
備考1. “超出0.1 wt %”及“超出0.01 wt %”係指限用物質之百分比含量超出百分比含量基準值。 Note 1: “Exceeding 0.1 wt %” and “exceeding 0.01 wt %” indicate that the percentage content of the restricted substance exceeds the reference percentage value of presence condition.						
備考2. “○”係指該項限用物質之百分比含量未超出百分比含量基準值。 Note 2: “○” indicates that the percentage content of the restricted substance does not exceed the percentage of reference value of presence.						
備考3. “—”係指該項限用物質為排除項目。 Note 3: The “—” indicates that the restricted substance corresponds to the exemption.						

表2 適用機種的型式與系列型式

TLB-50	型 式	TLB-50 1P 50/60Hz 50AF(15A,20A,30A,40A,50A)AC110-220V 兩用, I△n:15mA,30mA,100mA,300mA,500mA動作時間:高速型(0.1秒以內), Icu:10kA at110V,5kA at220V
	系列型式	TLB-50 2P 50/60Hz 50AF(15A,20A,30A,40A,50A)AC220V專用, I△n:15mA,30mA,100mA,300mA,500mA動作時間:高速型(0.1秒以內), Icu:10kA at220V,I <sub>su</sub> :2.5kA at127V
TLB-50EB	型 式	TLB-50EB Ue:1P+N為AC110V,220V兩用,2P為AC220V專用; 50/60Hz; 50AF; In:15,20,30,40,50A; I△n:15mA,30mA,100mA,300mA,500mA; 高速型(0.1秒以內) Icu:1P+N為5kA at 110V及220V, 2P為5kA at 220V; I <sub>su</sub> :1.3kA at 127V(2P用)
	系列型式	
TLB-50S (1P+N)	型 式	TLB-50S 1P+N Ue:AC110V-220V 60Hz; In:15A,20A,30A,40A,50A; 動作時間:0.1秒以內; I△n:15mA,30mA,100mA,300mA,500mA; Icu:15KA at 110V,10KA at 220V
	系列型式	KHB-150 1P+N Ue:AC110V-220V 60Hz; In:15A,20A,30A,40A,50A;動作時間:0.1秒以內; I△n:15mA,30mA,100mA,300mA,500mA;Icu:15KA at 110V,10KA at 220V

表2 適用機種的型式與系列型式(續)

TLB-50S (2P)	型 式	TLB-50S 2P額定電壓(Ue):AC220V專用,頻率:60Hz;額定電流(In):15A,20A,30A,40A,50A;接地故障保護、過負載保護及短路保護兼用;動作時間:高速型(0.1秒以內);額定靈敏度電流(I $\Delta$ n):15mA,30mA,100mA,300mA,500mA;額定短路容量(Icu):15KA at 220V;個別短路容量(Isu):3.8KA at 127V
	系列型式	KHB-250 2P額定電壓(Ue):AC220V專用,頻率:60Hz;額定電流(In):15A,20A,30A,40A,50A;接地故障保護、過負載保護及短路保護兼用;動作時間:高速型(0.1秒以內);額定靈敏度電流(I $\Delta$ n):15mA,30mA,100mA,300mA,500mA;額定短路
TLB-50P	型 式	TLB-50P 1P 15A,20A,30A 50/60Hz Ue:110-220VAC兩用 30mA 高速型 (0.1秒以內) Icu:10kA at 110V,5kA at 220V
	系列型式	TLB-50P 1P 15A,20A,30A,40A,50A 50AF 50/60Hz Ue:110-220VAC兩用 30mA 高速型(0.1秒以內) Icu:10kA at 220V, TLB-50P 2P 15A,20A,30A,40A 50/60Hz Ue:220VAC 30mA 高速型 (0.1秒以內) Icu:10kA at 220V Isu:2.5kA at 127V, TLB-50P 2P 50A 50AF 50/60Hz Ue:220VAC 30mA 高速型(0.1秒以內) Icu:10kA at 220V,Isu:2.5kA at 127V