

表1 限用物質含有情況超出百分比含量基準值之標示

東元電機股份有限公司						
設備名稱：無熔線斷路器，型號（型式）：請見表2 Equipment name Type designation (Type)		限用物質及其化學符號 Restricted substances and its chemical symbols				
單元 Unit	鉛 Lead (Pb)	汞 Mercury (Hg)	鎘 Cadmium (Cd)	六價鉻 Hexavalent chromium (Cr^{+6})	多溴聯苯 Polybrominated biphenyls (PBB)	多溴二苯醚 Polybrominated diphenyl ethers (PBDE)
外殼、把手、絕緣板	○	○	○	○	○	○
接點	○	○	—	○	○	○
內部機構及零件	○	○	○	超出 0.1wt%	○	○
螺絲、配件	○	○	○	超出 0.1wt%	○	○
機種差異零件	○	○	○	超出 0.1wt%	○	○

備考1. “超出 0.1 wt %” 及 “超出 0.01 wt %” 係指限用物質之百分比含量超出百分比含量基準值。
Note 1 : “Exceeding 0.1 wt %” and “exceeding 0.01 wt %” indicate that the percentage content of the restricted substance exceeds the reference percentage value of presence condition.

備考2. “○” 係指該項限用物質之百分比含量未超出百分比含量基準值。
Note 2 : “○” indicates that the percentage content of the restricted substance does not exceed the percentage of reference value of presence.

備考3. “—” 係指該項限用物質為排除項目。
Note 3 : The “—” indicates that the restricted substance corresponds to the exemption.

表2 適用機種的型式與系列型式

QLS	型式	QLS 1P Ui:440VAC 60Hz 100AF(15/20/30/40/50A) Icu:10kA at 110V ; Ics:5kA at 110V
	系列型式	QLS 2P Ui:440VAC 60Hz 100AF(100A) Icu:10kA at 220V ; Ics:5kA at 220V Isu:2.5kA at 127V, QLS 2P Ui:440VAC 60Hz 100AF(15/20/30/40/50/60/75A) Icu:10kA at 220V ; Ics:5kA at 220V ; Isu:2.5kA at 127V, QLS 3P Ui:440VAC 60Hz 100AF(15/20/30/40/50/60/75/100A) Icu:10kA at 220V ; Ics:5kA at 220V Isu:2.5kA at 127V
QLHH	型式	QLHH 1P Ue:AC110V,220V; 頻率:60Hz; 框架:100AF; In:15A,20A,30A,40A,50A; Icu:22kA at 110V,10kA at 220V; Ics:11kA at 110V,5kA at 220V。
	系列型式	QLHH 2P,3P Ue:AC220V,380V; 頻率:60Hz; 框架:100AF; In:15A,20A,30A,40A,50A,60A,75A,100A; Icu:22kA at 220V,10kA at 380V; Ics:11kA at 220V,5kA at 380V; Isu:2.5kA at 220V。