

Technical drawings of the TAB-3200 fixed type circuit breaker, showing dimensions in mm.

Front View (Top Left): Dimensions include 493 (四極), 378 (三極), 352, 258, 21, 13, 11, 211, 400 (三極), and 515 (四極).

Side View (Top Middle): Dimensions include 18min, 402, 50, 150, 69.5, 290, 389, 23, 92, 112, 115, and 40. Labels include "L 垂直接線" and "D".

Terminal View (Top Right): Dimensions include 72, 40, 86, 15, 40, 115, 115, 115, 96, and 16-Ø13. Labels include "N 極", "水平接線 (標準配置)", and "C".

Terminal View (Middle Right): Dimensions include 32, 50, 86, 18.5, 115, 115, 115, 96, and 12-Ø13. Labels include "N 極", "水平短端子", and "C".

Terminal View (Bottom Right): Dimensions include 115, 15, 40, 86, 115, 115, 115, 40, and 32-Ø13. Labels include "D", "N 極", "L 垂直接線", and "斷路器安裝板".

Mounting Plate View (Bottom Middle): Dimensions include 269, 362, 311, 28.5, 8-Ø4, 202.5, 405, and 2. Labels include "斷路器右安裝孔" and "面板開孔".

Mounting Plate View (Bottom Left): Dimensions include 4-Ø12, 150, 400 (三極), 515 (四極), and "斷路器右安裝孔".

In A	a mm
2000~3200	30

In A	a mm
2000~3200	30